# P/N 8617.200-55

## Motorized hose reels - s. 600

Hydraulic motor operated hose reel for hot water, 1400 psi, without hose, NPSM 1" (f) inlet - NPSM 1" (f) outlet



| | |
|---|---|
| FLUIDS | WATER |
| SECTORS | RAILWAY TRANSPORT \| MANUFACTURING INDUSTRY \| MINING \| SHIPPING AND OFFSHORE |

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 1400 |
| Compatible fluids | | water max 130 °C |
| Swivel joint | | AISI 304 stainless steel |
| Seals | | Viton® |
| Characteristic | | fixed |
| Material | | painted steel |
| Couplings | | - |
| Hose | | - |
| ø and hose length | ø - feet (') | - |
| Inlet | | NPSM 1" (f) |
| Outlet | | NPSM 1" (f) |
| Reel flow path | | brass - zinc plated steel |
| Drum width | inches (") | 7.2" |

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright ® 2019 All rights reserved to RAASM USA, Inc