P/N 90DV/21-55

Industrial pumps - s. 900

Divorced pump series 312, R 2:1 - 25 gpm with Viton® seals, 24.6"suction tube lenght

FLUIDS	FRESH OIL | ANTIFREEZE | DIESEL FUEL
SECTORS	MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE
CERTIFICATIONS	ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate		25.1 gpm
Ratio		2:1
Compatible fluids		chemical and industrial fluids
Suction tube upper body		carbon steel
Suction tube		carbon steel
Air inlet connection		NPT 1/2" (f)
Fluid outlet connection		NPT 1-1/2" (f)
Max supply pressure	psi	120
Max air consumption 120 psi	cfm	71
Noise level	dB	80
Suitable for drums or tank		modular - bulk tank
Packing	No. - ft3	1 - 4.2
Weight	lb	99

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright ® 2019 All rights reserved to RAASM USA, Inc