



P/N 91F/451-55

Industrial pumps - s. 900

Flanged pump series 312, R 45:1 - 9.7 lbs/min with polyurethane seals, 37" suction tube length, suitable for 400 lb drums



FLUIDS

FRESH OIL | GREASE

SECTORS

AERONAUTIC | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate		9.7 lb/min
Ratio		45:1
Compatible fluids		high viscosity oils and greases
Suction tube upper body		carbon steel
Suction tube		carbon steel
Air inlet connection		NPT 1/2" (f)
Fluid outlet connection		NPT 1/2" (f)
Max supply pressure	psi	120
Max air consumption 120 psi	cfm	63
Noise level	dB	80
Suitable for drums or tank		suitable for drums 400 lb
Packing	No. - ft3	1 - 2.5
Weight	lb	42

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906