



P/N 92608.102-55

Enclosed hose reels with polyurethane hose

Enclosed hose reels series 250 for air-water, 290 psi, with polyurethane hose 33' \varnothing 3/8", NPT 3/8" (m) inlet - NPT 3/8" (m) outlet



FLUIDS SECTORS

ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING
INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY

| Features | UM | Value |
|-------------------------------|--------------------------|-------------------------------|
| Pressure | psi | 300 |
| Compatible fluids | | air - water 40 °C |
| Swivel joint | | brass, swivelling hose outlet |
| Seals | | Viton® |
| Characteristic | | swivelling |
| Material | | painted steel |
| Couplings | | brass |
| Hose | | 972.110-55 |
| \varnothing and hose length | \varnothing - feet (') | 3/8" - 33' |
| Inlet | | NPTF 3/8" (m) |
| Outlet | | NPTF 3/8" (m) |
| Reel flow path | | brass - Delrin® |
| Drum width | inches (") | 4.9" |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc