P/N 92C/701-55

Industrial pumps - s. 900

Pneumatic pump series 312, R 70:1 - 6.6 lb/min with polyurethane seals, 29" suction tube lenght, suitable for 120 lb drums



FLUIDS FRESH OIL | GREASE

SECTORS AERONAUTIC | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | MANUFACTURING INDUSTRY | MINING | CENTRALIZED LUBRICATION SYSTEM | SHIPPING AND OFFSHORE

Features	UM	Value
Flow rate		6.6 lb/min
Ratio		70:1
Compatible fluids		high viscosity oils and greases
Suction tube upper body		carbon steel
Suction tube		carbon steel
Air inlet connection		NPT 1/2" (f)
Fluid outlet connection		NPT 1/2" (f)
Max supply pressure	psi	120
Max air consumption 120 psi	cfm	63
Noise level	dB	80
Suitable for drums or tank		suitable for drums 120 lb
Packing	No. - ft3	1 - 3.3
Weight	lb	40

RAASM USA, Inc
5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA
Phone. +1 704 370 1906 - Fax. +1 980 236 9365
Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright ® 2019 All rights reserved to RAASM USA, Inc