



P/N 93108.102-55

Enclosed hose reels with polyurethane hose

Enclosed hose reels series 300 for air-water, 290 psi, with polyurethane hose 40' ø 5/16", NPT 3/8" (m) inlet - NPT 1/4" (m) outlet



FLUIDS SECTORS

ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING
INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water 40 °C
Swivel joint		brass - Delrin®
Seals		Viton®
Characteristic		swivelling
Material		painted steel
Couplings		brass
Hose		971.112-55
ø and hose length	ø - feet (')	5/16" - 40'
Inlet		NPTF 3/8" (m)
Outlet		NPTF 1/4" (m)
Reel flow path		brass - Delrin®
Drum width	inches (")	4.9"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc