P/N 93108.103-55

Enclosed hose reels with polyurethane hose

Enclosed hose reels series 300 for air-water, 290 psi, with polyurethane hose 50' ø 5/16", NPT 3/8" (m) inlet - NPT 1/4" (m) outlet

FLUIDS ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water 40 °C
Swivel joint		brass - Delrin®
Seals		Viton®
Characteristic		swivelling
Material		painted steel
Couplings		brass
Hose		971.116-55
ø and hose length	ø - feet (')	5/16" - 50'
Inlet		NPTF 3/8" (m)
Outlet		NPTF 1/4" (m)
Reel flow path		brass - Delrin®
Drum width	inches (")	4.9"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc