# P/N 93108.105-55

## Enclosed hose reels with polyurethane hose

Enclosed hose reels series 300 for air-water, 290 psi, with polyurethane hose 40' ø 3/8", NPT 3/8" (m) inlet - NPT 3/8" (m) outlet



**FLUIDS** ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 300 |
| Compatible fluids | | air - water 40 °C |
| Swivel joint | | brass - Delrin® |
| Seals | | Viton® |
| Characteristic | | swivelling |
| Material | | painted steel |
| Couplings | | brass |
| Hose | | 972.112-55 |
| ø and hose length | ø - feet (') | 3/8" - 40' |
| Inlet | | NPTF 3/8" (m) |
| Outlet | | NPTF 3/8" (m) |
| Reel flow path | | brass - Delrin® |
| Drum width | inches (") | 4.9" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc