



P/N 93208.105-55

Enclosed hose reels with polyurethane hose

AISI 304 stainless steel enclosed hose reels series 300 for air-water, 290 psi, with polyurethane hose 40' \varnothing 3/8", NPT 3/8" (m) inlet - NPT 3/8" (m) outlet



FLUIDS SECTORS

ANTIFREEZE | WINDSHIELD FLUID | AIR | WATER | NITROGEN/INFLATING USE | CLEANING DETERGENT
AGRICULTURE | CLEANING | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water 70 °C
Swivel joint		AISI 304 stainless steel - Delrin®
Seals		Viton®
Characteristic		swivelling
Material		AISI 304 stainless steel
Couplings		AISI 304 stainless steel
Hose		982.112-55
\varnothing and hose length	\varnothing - feet (')	3/8" - 40'
Inlet		NPTF 3/8" (m)
Outlet		NPTF 3/8" (m)
Reel flow path		AISI 304 stainless steel - Delrin®
Drum width	inches (")	4.9"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906