P/N 93208.105-55

Enclosed hose reels with polyurethane hose

AISI 304 stainless steel enclosed hose reels series 300 for air-water, 290 psi, with polyurethane hose 40' ø 3/8", NPT 3/8" (m) inlet - NPT 3/8" (m) outlet



FLUIDS	ANTIFREEZE | WINDSHIELD FLUID | AIR | WATER | NITROGEN/INFLATING USE | CLEANING DETERGENT
SECTORS	AGRICULTURE | CLEANING | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water 70 °C
Swivel joint		AISI 304 stainless steel - Delrin®
Seals		Viton®
Characteristic		swivelling
Material		AISI 304 stainless steel
Couplings		AISI 304 stainless steel
Hose		982.112-55
ø and hose length	ø - feet (')	3/8" - 40'
Inlet		NPTF 3/8" (m)
Outlet		NPTF 3/8" (m)
Reel flow path		AISI 304 stainless steel - Delrin®
Drum width	inches (")	4.9"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc