# P/N 9430.102-55

## Hose reels with ABS drum - s. 430-440

Hose reel series 430 ABS for air-water, 300 psi, with hose 60' ø 3/8", NPSM 1/2" (f) inlet - NPTF 3/8" (m) outlet



**FLUIDS** FRESH OIL | ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

**CERTIFICATIONS** ATEX (ZONE 2) | ATEX (ZONE 22)

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 300 |
| Compatible fluids | | air - water |
| Swivel joint | | brass |
| Seals | | Viton® |
| Characteristic | | fixed |
| Material | | painted steel with ABS drum |
| Couplings | | zinc plated steel |
| Hose | | 995.217-55 |
| ø and hose length | ø - feet (') | 3/8" - 60' |
| Inlet | | NPSM 1/2" (f) |
| Outlet | | NPTF 3/8" (m) |
| Reel flow path | | brass - zinc plated steel |
| Drum width | inches (") | 4.5" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc