



P/N 9430.300-55

Hose reels with ABS drum - s. 430-440

Hose reel series 430 ABS for hot water, 3000 psi,
without hose, NPSM 3/8" (f) inlet - NPSM 3/8" (f) outlet



FLUIDS

WATER

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND
ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

| Features | UM | Value |
|-------------------|--------------|--|
| Pressure | psi | 3000 |
| Compatible fluids | | water max 130 °C |
| Swivel joint | | AISI 304 stainless steel |
| Seals | | Viton® |
| Characteristic | | fixed |
| Material | | painted steel with ABS drum |
| Couplings | | - |
| Hose | | - |
| Ø and hose length | Ø - feet (') | - |
| Inlet | | NPSM 3/8" (f) |
| Outlet | | NPSM 3/8" (f) |
| Reel flow path | | AISI 304 stainless steel - zinc plated steel |
| Drum width | inches (") | 4.5" |

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc