# P/N 9430.400-55

## Hose reels with ABS drum - s. 430-440

Hose reel series 430 ABS for oil and similar, 2000 psi, without hose, NPSM 1/2" (f) inlet - NPSM 1/2" (f) outlet



**FLUIDS** FRESH OIL | ANTIFREEZE

**SECTORS** AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

**CERTIFICATIONS** ATEX (ZONE 2) | ATEX (ZONE 22)

| Features | UM | Value |
|---|---|---|
| Pressure | psi | 2000 |
| Compatible fluids | | oils and allied products |
| Swivel joint | | zinc plated steel |
| Seals | | polyurethane |
| Characteristic | | fixed |
| Material | | painted steel with ABS drum |
| Couplings | | - |
| Hose | | - |
| ø and hose length | ø - feet (') | - |
| Inlet | | NPSM 1/2" (f) |
| Outlet | | NPSM 1/2" (f) |
| Reel flow path | | zinc plated steel |
| Drum width | inches (") | 4.5" |

**RAASM USA, Inc**
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com



Copyright ® 2026 All rights reserved to RAASM USA, Inc