P/N 9430.402-55

Hose reels with ABS drum - s. 430-440

Hose reel series 430 ABS for oil and similar, 2000 psi, with hose 50' ø 1/2", NPTF 1/2" (m) inlet - NPTF 1/2" (m) outlet



FLUIDS FRESH OIL | ANTIFREEZE

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	2000
Compatible fluids		oils and allied products
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel with ABS drum
Couplings		zinc plated steel
Hose		996.315-55
ø and hose length	ø - feet (')	1/2" - 50'
Inlet		NPTF 1/2" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	4.5"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc