P/N 9430.415-55

Hose reels with ABS drum - s. 430-440

Hose reel series 430 ABS for oil and similar, 1450 psi, without hose, NPSM 1/2" (f) inlet - NPSM 1/2" (m) outlet



FLUIDS FRESH OIL | ANTIFREEZE

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	1400
Compatible fluids		water max 130 °C, oils and allied products
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel with ABS drum
Couplings		-
Hose		-
ø and hose length	ø - feet (')	-
Inlet		NPSM 1/2" (f)
Outlet		NPSM 1/2" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	4.5"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc