



# P/N 9430.500-55

## Hose reels with ABS drum - s. 430-440

Hose reel series 430 ABS for oil and similar, 5800 psi, without hose, NPSM 3/8" (f) inlet - NPSM 3/8" (f) outlet



### FLUIDS

GREASE

### SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

### CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	5800
Compatible fluids		grease
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel with ABS drum
Couplings		-
Hose		-
Ø and hose length	Ø - feet (')	-
Inlet		NPSM 3/8" (f)
Outlet		NPSM 3/8" (f)
Reel flow path		zinc plated steel
Drum width	inches (")	4.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906