P/N 9432.100-55

Hose reels with ABS drum - s. 430-440

Stainless steel hose reel for air-water, 300 psi, without hose, NPSM 1/2" (f) inlet - NPSM 1/2" (f) outlet



FLUIDS FRESH OIL | ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE | A1 JET (FUEL FOR PLANES)

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water
Swivel joint		brass
Seals		Viton®
Characteristic		fixed
Material		AISI 304 stainless steel with ABS drum
Couplings		-
Hose		-
ø and hose length	ø - feet (')	-
Inlet		NPSM 1/2" (f)
Outlet		NPSM 1/2" (f)
Reel flow path		brass - AISI 304 stainless steel
Drum width	inches (")	4.5"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc