



# P/N 9432.202-55

## Hose reels with ABS drum - s. 430-440

Stainless steel hose reel for hot water, 1400 psi, hose 50'  $\varnothing$  1/2", NPTF 1/2" (m) inlet - NPTF 1/2" (m) outlet



### FLUIDS

WATER

### SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | SHIPPING AND OFFSHORE

### CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	1400
Compatible fluids		water max 130 °C
Swivel joint		AISI 304 stainless steel
Seals		Viton®
Characteristic		fixed
Material		AISI 304 stainless steel with ABS drum
Couplings		zinc plated steel
Hose		996.316-55
$\varnothing$ and hose length	$\varnothing$ - feet (')	1/2" - 50'
Inlet		NPTF 1/2" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		AISI 304 stainless steel
Drum width	inches (")	4.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc