



P/N 9450.100-55

Hose reels with ABS drum - s. 430-440

Enclosed hose reel series 450 for air-water, 300 psi,
without hose, NPSM 1/2" (f) inlet - NPSM 1/2" (f) outlet



FLUIDS

FRESH OIL | ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE | A1 JET (FUEL FOR PLANES)

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND
ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water
Swivel joint		brass
Seals		Viton®
Characteristic		fixed
Material		painted steel with ABS drum
Couplings		-
Hose		-
Ø and hose length	Ø - feet (')	-
Inlet		NPSM 1/2" (f)
Outlet		NPSM 1/2" (f)
Reel flow path		brass - zinc plated steel
Drum width	inches (")	5.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906

info@raasmusa.com - www.raasmusa.com

Copyright © 2019 All rights reserved to RAASM USA, Inc