



# P/N 9450.103-55

## Hose reels with ABS drum - s. 430-440

Enclosed hose reel series 450 for air-water, 300 psi, hose 35' ø 1/2", NPTF 1/2" (m) inlet - NPTF 1/2" (m) outlet



### FLUIDS

FRESH OIL | ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

### SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

### CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water
Swivel joint		brass
Seals		Viton®
Characteristic		fixed
Material		painted steel with ABS drum
Couplings		zinc plated steel
Hose		996.210-55
ø and hose length	ø - feet (')	1/2" - 35'
Inlet		NPTF 1/2" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		brass - zinc plated steel
Drum width	inches (")	5.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906