P/N 9450.104-55

Hose reels with ABS drum - s. 430-440

Enclosed hose reel series 450 for air-water, 300 psi, hose 50' ø 1/2", NPTF 1/2" (m) inlet - NPTF 1/2" (m) outlet



FLUIDS FRESH OIL | ANTIFREEZE | AIR | WATER | NITROGEN/INFLATING USE

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	300
Compatible fluids		air - water
Swivel joint		brass
Seals		Viton®
Characteristic		fixed
Material		painted steel with ABS drum
Couplings		zinc plated steel
Hose		996.215-55
ø and hose length	ø - feet (')	1/2" - 50
Inlet		NPTF 1/2" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		brass - zinc plated steel
Drum width	inches (")	5.5"

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc