



P/N 9450.401-55

Hose reels with ABS drum - s. 430-440

Enclosed hose reel series 450 for oil and similar, 2000 psi, hose 35' \varnothing 1/2", NPTF 1/2" (m) inlet - NPTF 1/2" (m) outlet



FLUIDS

FRESH OIL | ANTIFREEZE

SECTORS

AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | BUILDING INDUSTRY AND ROAD CONSTRUCTION | MANUFACTURING INDUSTRY

CERTIFICATIONS

ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Pressure	psi	2000
Compatible fluids		oils and allied products
Swivel joint		zinc plated steel
Seals		polyurethane
Characteristic		fixed
Material		painted steel with ABS drum
Couplings		zinc plated steel
Hose		996.310-55
\varnothing and hose length	\varnothing - feet (')	1/2" - 35'
Inlet		NPTF 1/2" (f)
Outlet		NPTF 1/2" (m)
Reel flow path		zinc plated steel
Drum width	inches (")	5.5"

RAASM USA, Inc

5531 Equipment Drive, Suite B - Charlotte, NC 28262 USA

Phone. +1 704 370 1906 - Fax. +1 980 236 9365

Toll free number. +1 8773701906