P/N 95D/61-55

AISI 304 stainless steel industrial pumps

AISI 304 stainless steel divorced pump series 312, R 6:1 - 11 gpm, with Teflon® seals, 18.9" suction tube lenght, modular



FLUIDS ANTIFREEZE | WINDSHIELD FLUID | WATER | DEF | PAINT | CLEANING DETERGENT

SECTORS AERONAUTIC | AGRICULTURE | AUTOMOTIVE | LUBE TRUCK AND INDUSTRIAL VEHICLE | CLEANING | BUILDING INDUSTRY AND ROAD CONSTRUCTION | RAILWAY TRANSPORT | CHEMICAL INDUSTRY | MANUFACTURING INDUSTRY | MINING | SHIPPING AND OFFSHORE

CERTIFICATIONS ATEX (ZONE 2) | ATEX (ZONE 22)

Features	UM	Value
Flow rate	gpm	11
Ratio		6:1
Compatible fluids		paints, chemical and industrial fluids
Suction tube upper body		AISI 304 stainless steel
Suction tube		AISI 304 stainless steel
Air inlet connection		NPT 1/2" (f)
Fluid inlet connection		NPT 1" (f)
Fluid outlet connection		NPT 3/4" (f)
Max air consumption 120 psi	cfm	64
Noise level	dB	80
Max supply pressure	psi	120
Suitable for drums or tanks		modular
Packing	No. - ft3	1 - 2.0
Weight	lb	37

RAASM USA, Inc
28 N Ann Street #100 Asheville, NC 28801 USA
Phone. +1 704 370 1906
orders@raasmusa.com

Copyright ® 2026 All rights reserved to RAASM USA, Inc